Approximate Matches

Program File: `mismatch.pas, mismatch.c, or mismatch.cpp`
Input File: `mismatch.in`
Output File: `mismatch.out`

Given a non-null string of text S, a non-null string of text P, and an integer $k \geq 0$, find all non-null substrings of S that match or "approximately match" P with at most k mismatches. The substring S_1 is considered to *match* the string P if they are identical (as you might expect), and *approximately match* if the strings differ by no more than k mismatches, as defined next.

If a minimum of m characters have to be removed from S_1 to make it identical to P, then S_1 approximately matches P with m mismatches. If a minimum of n characters have to be removed from P to make it identical to S_1, then S_1 approximately matches P with n mismatches. If m characters have to be removed from S_1 and n characters have to be removed from P to make S_1 and P identical, then S_1 approximately matches P with $m+n$ mismatches (here $m+n$ should be minimized).

Consider the string S = "`The sky is blue`".

- The substring "`The sky`" in S matches the string "`The sky`".
- The substring "`The sky`" in S approximately matches the string "`The skye`" with one mismatch (the extra "`e`" in the string).
- The substring "`sky is`" in S approximately matches the string "`skis`" with two mismatches (the characters "`y`" and "` `" in the substring).
- The substring "`sky is`" in S approximately matches the string "`tennis`" with eight mismatches (four characters are removed from "`sky is`" and four are removed from "`tennis`").

As another example, the string "`scrapple`" approximately matches the string "`apples`" with four mismatches (by removing `s`, `c`, `r` from "`scrapple`" and `s` from "`apples`"). Although there are other ways to remove letters from these two strings to make the results identical (for example removing all but the `s` from both strings), four characters is the minimum number that can be removed.

Note that case is important in this problem; thus `T` does not match `t`, but `T` approximately matches `t` with two mismatches.

Input

Each data set consists of three lines that contain k, S, and P, respectively. k is an integer; S is a string of length between 1 and 50 inclusive, and P is a string of length between 1 and 20 inclusive. Your program must stop processing data when it encounters a negative value for k.

Output

For each match with i mismatches ($0 \le i \le k$), your program must generate a line of one of the following forms (whichever is appropriate):

```
Q matches P
Q matches P with 1 mismatch
Q matches P with i mismatches
```

where Q is a substring of S that matches P or that approximately matches P with i mismatches. If more than one substring in S matches or approximately matches P, they must be printed in the order they appear in S (from left to right). Substrings that start at the same position must be listed in the order of their size (shortest to longest). No value for Q may be listed more than once. If there is no match, no output should be generated. Leave a blank line after the output for each data set (even if there is no output for the data set).

Sample Input

```
1
He did not care about the carpet in the car.
car
2
ABC
BC
-1
```

Sample Output

```
 car matches car with 1 mismatch
ca matches car with 1 mismatch
car matches car
care matches car with 1 mismatch
ar matches car with 1 mismatch
carp matches car with 1 mismatch
car. matches car with 1 mismatch

AB matches BC with 2 mismatches
ABC matches BC with 1 mismatch
B matches BC with 1 mismatch
BC matches BC
C matches BC with 1 mismatch
```